



PALISADE® ASPHALT FLASHING

PROTECTION OF DOOR & WINDOW OPENINGS FROM WATER INTRUSION

Palisade Asphalt Flashing is a self-adhered flashing membrane comprised of a flexible polyethylene (PE) film coated with rubberized asphalt adhesive. The rolls come with an easy-to-remove film release liner.

FEATURES & BENEFITS

- Creates a smooth watertight surface around nails, staples and fasteners
- Meets all AAMA 711-13 requirements, Type A, Level 3 (176°F)
- Seals around fasteners and nails (ASTM D1970)
- Water and tear resistance
- Good adhesion on most surfaces (Use of J-Roller recommended)
- Excellent elongation and elasticity
- Up to 4 months exposure
- Application Temperature Range 40°F to 122°F
- Service Temperature Range -40°F to 176°F



800-565-2000 | palisadebuild.com



PRODUCT ATTRIBUTES

CHARACTERISTICS				
Product Code	4200475	4200675	4200975	4201275
Dimension (in x yd)	4" x 75'	6" x 75'	9" x 75'	12" x 75'
Rolls/Case	12	8	4	4
Product UPC	0-77922-42004-9	0-77922-42006-3	0-77922-42009-4	0-77922-42012-4
Release Liner	Grey film	Grey film - Split Release	Grey film - Split Release	Grey film - Split Release
Adhesive	SBS Modified Asphalt	SBS Modified Asphalt	SBS Modified Asphalt	SBS Modified Asphalt
Facer	Polyethylene Film	Polyethylene Film	Polyethylene Film	Polyethylene Film
Color	White with blue print	White with blue print	White with blue print	White with blue print
Thickness	25 mil	25 mil	25 mil	25 mil
Tensile	13 lb/inch	13 lb/inch	13 lb/inch	13 lb/inch
Adhesion to Steel	79 oz/inch	79 oz/inch	79 oz/inch	79 oz/inch
Elongation	500%	500%	500%	500%
Case UPC	5-00-77922-42004-4	5-00-77922-42006-8	5-00-77922-42009-9	5-00-77922-42012-9



PRODUCT APPLICATIONS

- Waterproof flashing membrane used to seal window and door openings
- Recommend on aluminum, wood, wood clad, fiberglass, vinyl windows and doors
- Recommend on most house wraps, OSB, exterior gypsum and fibre board
- All above surfaces have to be dry and clean in order to assure proper contact

MARKETS

- Building and Construction

LIMITATIONS

- Asphalt flashing is not compatible with some sealants and caulks containing plasticizers or solvents
- Asphalt flashing is not compatible with flexible vinyl, PVC membranes or EPDM



Scan for more info or visit palisadebuild.com

