

PLASTIC SHEETING

TRANSPARENT PROTECTIVE FILM

Used during vehicle repairs and general surface protection applications, this product protects vehicles and other surfaces from overspray and other potential contaminants.



FEATURES & BENEFITS



Tear-resistant



Transparent plastic



nt Static cling



Easy to dispense via box

	\frown	
+		$ \rangle$
		×

Helps maintain clean work environment



Cost effective

AVAILABLE IN ULTRA & PERFORMANCE







888-898-7834 | itape.com

PRODUCT ATTRIBUTES

RESOURCE NUMBER	SIZE	BACKING	THICKNESS	COLOR	ΜΟΩ
US16400	16ft x 400ft	Polyethylene sheeting/film	.375 mil	Clear	12 rolls (mix & match) 1 week leadtime
PS16400	16ft x 400ft	Polyethylene sheeting/film	.3 mil	Clear	12 rolls (mix & match) 1 week leadtime
US20250	20ft x 250ft	Polyethylene sheeting/film	.375 mil	Clear	12 rolls (mix & match) 1 week leadtime

PRODUCT INSTRUCTIONS

Should only be applied to clean, dry, thoroughly cured surfaces. If surfaces are dirty, wash and dry before applying plastic sheeting.

NOTE: Do not apply to wet or dirty vehicles or finishes that are not fully cured.

- 1. Ensure application surface is clean and dry
- 2. Apply plastic sheeting film to intended surface
- 3. Tape down all perimeters. Masking tape is suggested for this, but not required
- 4. Cut / trim film to fit desired area
- 5. Remove film from application area (carefully) once job is done

MARKETS

- Automotive Aftermarket
- DIY Home Renovations
- Building and Construction



Scan for more info or visit itape.com/american

